


Electrical specifications			
Frequency Range(MHz)	1710~2170×2		
	1710~1880	1850~1990	1920~2170
Polarization	±45°		
Gain (dBi)	17.2±0.5	17.5±0.5	17.8±0.5
Horizontal 3dB beamwidth (°)	64±2.7	64±2.3	65±1.9
Vertical 3dB beamwidth (°)	7.3±0.4	6.7±0.4	6.3±0.5
Front-to-back ratio (dB)	>28	>28	>28
Cross-polar ratio (dB)	>22 (0°)	>22 (0°)	>22 (0°)
Electrical downtilt (°)	2~12		
Sidelobe suppression (dB) (First sidelobe above main beam)	>18	>18	>17
VSWR	<1.5		
Isolation: intra-system (dB)	>28		
Isolation: inter-system (dB)	>30		
Intermodulation IM3 (2×43dBm carrier)	≤-153dBc		
Impedance (Ω)	50		
Max. power per input (W) @50°C	250		
RET Model	TRCU-TQ10P2V01(Replaceable, Included)		
RET Protocol	AISG 2.0 SRET		
Lightning protection	Dc Ground		

Mechanical specifications	
Connector	4×4.3-10-Female
Connector position	Bottom
Height×width×depth (mm)	1360×320×105
Packing size (mm)	1625×420×205
Antenna weight (kg)	14
Installation kit weight (kg)	5.4
Packing weight (kg)	22
Wind load (N, at 150km/h) Frontal/Lateral/Rearside	480/111/537
Max. wind velocity (km/h)	216
Radome material	Fiberglass
Radome color	Gray
Mechanical tilt (°)	0~15
Operating temperature (°C)	-50~65
Mounting hardware (mm)	Φ50~Φ115



1710~2170MHz

